




Volver al Índice

RSR

Paneles Led


PLAFÓN T8 IP20


IP20

1/10



DIMENSIONES	CÓDIGO	CCT (°K)	POTENCIA (W)	LÚMENES (lm)	P.V.P
 L 600	5103	3000	18 W	1620 lm	13,50 €
	5104	4500			
	5106	6000			
 L 900	5133	3000	24 W	2160 lm	17,00 €
	5134	4500			
	5136	6000			
 L 1200	5113	3000	40 W	3600 lm	20,00 €
	5114	4500			
	5116	6000			
 L 1500	5123	3000	50 W	4500 lm	32,00 €
	5124	4500			
	5126	6000			


**PLAFÓN T8 IP20
"CUADRADO"**


IP20

1/10




DIMENSIONES	CÓDIGO	CCT (°K)	POTENCIA (W)	LÚMENES (lm)	P.V.P
 L 600	5103.1	3000	24 W	2640 lm	24,99 €
	5104.1	4500			
	5106.1	6000			
 L 900	5133.1	3000	36 W	3960 lm	29,00 €
	5134.1	4500			
	5136.1	6000			
 L 1200	5113.1	3000	54 W	5940 lm	34,00 €
	5114.1	4500			
	5116.1	6000			
 L 1500	5124.1	4500	72 W	7920 lm	45,00 €
	5126.1	6000			



PLAFÓN T8 IP20
"de UNIÓN-INSERTABLES"

TIPO	VOLTAJE	MATERIAL	RF.	C.R.I.	Lm/W	TIPO LED	APERTURA
SUPERFICIE	220-240Vac	ALUMINIO TERMO	≥0,60	>80	90	SMD	110°


IP20

1/10




DIMENSIONES	CÓDIGO	CCT (°K)	POTENCIA (W)	LÚMENES (lm)	P.V.P
 L 600	5103.2	3000	18 W	1620 lm	16,50 €
	5104.2	4500			
	5106.2	6000			
 L 900	5133.2	3000	24 W	2160 lm	19,95 €
	5134.2	4500			
	5136.2	6000			
 L 1200	5113.2	3000	40 W	3600 lm	24,00 €
	5114.2	4500			
	5116.2	6000			
 L 1500	5124.2	4500	50 W	4500 lm	36,00 €
	5126.2	6000			


ACCESORIOS


CÓDIGO	DESCRIPCIÓN	P.V.P
5100	UNIÓN LINEAL	0,75 €
5101	UNIÓN LINEAL 500 mm	0,95 €
5102	UNIÓN LINEAL 1000 mm	1,15 €


VOLANTE LED E27 SUP. 24W

TIPO	VOLTAJE	MATERIAL	RF.	C.R.I.	Lm/W	TIPO LED	APERTURA
REDONDO	220-240Vac	ALUMINIO PLÁSTICO	≥0,50	>80	100	SMD 2835	160°



1/40


IP20


CÓDIGO	CCT (°K)	POTENCIA (W)	LÚMENES (lm)	P.V.P
5144	4500	24W	2400 lm	19,95 €
5146	6000			


ADAPTADOR E27
(INCLUIDO)


PANTALLA ESTANCA IP65

TIPO	VOLTAJE	MATERIAL	RF.	C.R.I.	Lm/W	TIPO LED	APERTURA
ESTANCA	220-240Vac	ALUMINIO TERMO	≥0,60	>80	80	SMD	120°



IP65


1/10



DIMENSIONES	CÓDIGO	CCT (°K)	POTENCIA (W)	LÚMENES (lm)	P.V.P
	5264	4500	18 W	1440 lm	19,50 €
	5266	6000			
	5274	4500	36 W	2880 lm	29,50 €
	5276	6000			
	5284	4500	48 W	3840 lm	49,50 €
	5286	6000			


PANTALLA ESTANCA IP65 SERIE G

TIPO	VOLTAJE	MATERIAL	RF.	C.R.I.	Lm/W	TIPO LED	APERTURA
ESTANCA	220-240Vac	ALUMINIO TERMO	≥0,90	>70	80	SMD	120°



IP65


1/10

DIMENSIONES	CÓDIGO	CCT (°K)	POTENCIA (W)	LÚMENES (lm)	P.V.P
	5314	4500	18 W	1440 lm	19,50 €
	5316	6000			
	5324	4500	36 W	2880 lm	29,50 €
	5326	6000			
	5334	4500	48 W	3840 lm	49,50 €
	5336	6000			




**PANEL DECORATIVO
CRISTAL**

TIPO	VOLTAJE	MATERIAL	PF.	C.R.I.	Lm/W	TIPO LED	APERTURA
EMPOTRABLE	220-240Vac	ALUMINIO CRISTAL	≥0,60	>80	70	SMD 2835	120°




IP54

1/20



CÓDIGO	CCT (°K)	POTENCIA (W)	LÚMENES (lm)	P.V.P
Ø120 Corte: 105 6204	4500	6 W	420 lm	13,95 €
Ø170 Corte: 155 6224	4500	12 W	840 lm	18,50 €
Ø225 Corte: 205 6244	4500	18 W	1260 lm	25,00 €

**PANEL ALUMINIO
REDONDO-BLANCO**


IP40


 Ø120
 Corte: 105
 1/40

 Ø170
 Corte: 155
 1/30


 Ø225
 Corte: 205
 1/20

 Ø300
 Corte: 280
 1/20

TIPO	VOLTAJE	MATERIAL	P.F.	C.R.I.	Lm/W	TIPO LED	APERTURA
EMPOTRABLE	85-240Vac	ALUMINIO	≥0,60	>80	80	SMD 2835	120°

CÓDIGO	CCT (°K)	POTENCIA (W)	LÚMENES (lm)	P.V.P
6003	3000	6 W	480 lm	5,50 €
6004	4500			
6006	6000			
6013	3000	12 W	960 lm	9,60 €
6014	4500			
6016	6000			
6023	3000	20 W	1600 lm	10,99 €
6024	4500			
6026	6000			
6033	3000	25 W	2000 lm	19,95 €
6034	4500			
6036	6000			

Isolated Driver


**PANEL ALUMINIO
REDONDO-NIQUEL**


IP40


 Ø120
 Corte: 105
 1/40

 Ø170
 Corte: 155
 1/30

 Ø225
 Corte: 205
 1/20

TIPO	VOLTAJE	MATERIAL	P.F.	C.R.I.	Lm/W	TIPO LED	APERTURA
EMPOTRABLE	85-240Vac	ALUMINIO	≥0,60	>80	80	SMD 2835	120°

CÓDIGO	CCT (°K)	POTENCIA (W)	LÚMENES (lm)	P.V.P
6003.1	3000	6 W	480 lm	7,99 €
6004.1	4500			
6006.1	6000			
6013.1	3000	12 W	960 lm	12,00 €
6014.1	4500			
6016.1	6000			
6023.1	3000	20 W	1600 lm	14,99 €
6024.1	4500			
6026.1	6000			

Isolated Driver



CÓDIGO	DIMMABLE	POTENCIA (W)	P.F.	P.V.P
6000		6 W	0,60	2,40 €
6010		12 W	0,60	2,95 €
6020		20 W	0,60	3,60 €
6022		18/20 W	0,98	5,50 €
6030		24/25 W	0,60	6,95 €
6032		24/25 W	0,98	8,95 €


VALIDO PARA TODOS LOS PANELES

**PANEL ALUMINIO
REDONDO-CROMO**


Ø120
Corte: 105
1/40

Ø170
Corte: 155
1/30

Ø225
Corte: 205
1/20



IP40



TIPO	VOLTAJE	MATERIAL	RF.	C.R.I.	Lm/W	TIPO LED	APERTURA
EMPOTRABLE	85-240Vac	ALUMINIO	≥0,60	>80	80	SMD 2835	120°

CÓDIGO	CCT (°K)	POTENCIA (W)	LÚMENES (lm)	P.V.P
6003.2	3000	6 W	480 lm	7,99 €
6004.2	4500			
6006.2	6000			
6013.2	3000	12 W	960 lm	12,00 €
6014.2	4500			
6016.2	6000			
6023.2	3000	20 W	1600 lm	14,99 €
6024.2	4500			
6026.2	6000			


Isolated Driver


**PANEL ALUMINIO
REDONDO-CUERO**


Ø120
Corte: 105
1/40

Ø170
Corte: 155
1/30

Ø225
Corte: 205
1/20



IP40



TIPO	VOLTAJE	MATERIAL	RF.	C.R.I.	Lm/W	TIPO LED	APERTURA
EMPOTRABLE	85-240Vac	ALUMINIO	≥0,70	>80	80	SMD 2835	120°


CÓDIGO	CCT (°K)	POTENCIA (W)	LÚMENES (lm)	P.V.P
6003.3	3000	6 W	480 lm	8,99 €
6004.3	4500			
6006.3	6000			
6013.3	3000	12 W	960 lm	13,00 €
6014.3	4500			
6016.3	6000			
6023.3	3000	20 W	1600 lm	16,00 €
6024.3	4500			
6026.3	6000			

Isolated Driver



CÓDIGO	DIMMABLE	POTENCIA (W)	P.F.	P.V.P
6001		6 W	0,60	7,25 €
6011		12 W	0,60	8,50 €
6021		18/20 W	0,60	10,00 €
6031		24/25 W	0,60	15,00 €

VALIDO PARA TODOS LOS PANELES

**PANEL ALUMINIO
CUADRADO-BLANCO**

IP40

L120
Corte: 105
1/40

L170
Corte: 155
1/30


L225
Corte: 205
1/20

L300
Corte: 280
1/20

TIPO	VOLTAJE	MATERIAL	RF.	C.R.I.	Lm/W	TIPO LED	APERTURA
EMPOTRABLE	85-240Vac	ALUMINIO	≥0,60	>80	80	SMD 2835	120°

CÓDIGO	CCT (°K)	POTENCIA (W)	LÚMENES (lm)	P.V.P
6503	3000	6 W	480 lm	5,95 €
6504	4500			
6506	6000			
6513	3000	12 W	960 lm	10,00 €
6514	4500			
6516	6000			
6523	3000	20 W	1600 lm	12,00 €
6524	4500			
6526	6000			
6533	3000	25 W	2000 lm	21,00 €
6534	4500			
6536	6000			

Isolated Driver

**PANEL ALUMINIO
CUADRADO-NIQUEL**

IP40

L120
Corte: 105
1/40

L170
Corte: 155
1/30

L225
Corte: 205
1/20

TIPO	VOLTAJE	MATERIAL	RF.	C.R.I.	Lm/W	TIPO LED	APERTURA
EMPOTRABLE	85-240Vac	ALUMINIO	≥0,60	>80	80	SMD 2835	120°

CÓDIGO	CCT (°K)	POTENCIA (W)	LÚMENES (lm)	P.V.P
6503.1	3000	6 W	480 lm	8,99 €
6504.1	4500			
6506.1	6000			
6513.1	3000	12 W	960 lm	13,00 €
6514.1	4500			
6516.1	6000			
6523.1	3000	20 W	1600 lm	16,00 €
6524.1	4500			
6526.1	6000			

Isolated Driver


CÓDIGO	DIMMABLE	POTENCIA (W)	P.F.	P.V.P
6000		6 W	0,60	2,40 €
6010		12 W	0,60	2,95 €
6020		20 W	0,60	3,60 €
6022		18/20 W	0,98	5,50 €
6030		24/25 W	0,60	6,95 €
6032		24/25 W	0,98	8,95 €

VALIDO PARA TODOS LOS PANELES

